



NOTE:
 Safety slide switch must be set to SWING safety.
 Swing logic on the Gyrotech analog control will slow the door only (not stop).
 When the door is fully closed and a person is detected in the swing area, upon activation the door will creep open.

NOTE:
 For Knowing Act applications all activating devices must connect to the purple wires of the OC-904. The OC-904 purple wires connect in parallel. Be sure to observe polarity (+ to +, - to -).

Dipswitch Settings	OFF	ON
1. Safety Output	N.O.	N.C.
2. Stall Output	N.O.	N.C.
3. Auto/K.A.	Automatic	Knowing Act
4. Force		
Fully Automatic		Knowing Act
1. OFF	1. OFF	
2. OFF	2. OFF	
3. OFF	3. ON	
4. OFF	4. OFF	

- INSTALLATION NOTES**
1. Set door speeds and verify proper door operation prior to final connections of sensors system.
 2. Technician MUST WALK TEST to verify function and detection patterns comply with ANSI/BHMA A156.10 requirements.

Title: Gyrotec 300/400 Sim Pair w/ Elite		Drawing # 01DORASTELI02
Drawing By: JAS	Date: 06-26-08	Sheet: 1 of 1
Optex Technologies Inc. 3882 Del Amo Blvd., Suite 604, Torrance, CA 90503 Office: (800)877-6656, Fax: (310)214-8655		